

ELMORE STOUTT SCHOOL

RESUME OF LIGHTS AND FANS QUANTITIES

ITEM NO	DESCRIPTION	UNIT	TOTAL	BLOCKS				
				A	B1	B2	C	EX
FANS								
1	BIG ASS CEILING FAN MODEL I6. 72 INCHES DIAMETER. 6" INCHES MOUNTING ROD. SOUND LEVEL <35 db AT MAX SPEED. 110 V 60 Hz 42W 1 PHASE. INDOOR USE. WHITE FINISH. WITH WALL MOUNTED CONTROLLER. NO LIGHT. INCLUDING FAN CONTROL SWITCH AND CONNECTIONS.	Item	24	0	12	12	0	0
2	BIG ASS CEILING FAN MODEL I6. 60 INCHES DIAMETER. 6" INCHES MOUNTING ROD. SOUND LEVEL <35 db AT MAX SPEED. 110 V 60 Hz 35W 1 PHASE. INDOOR USE. WHITE FINISH. WITH WALL MOUNTED CONTROLLER. NO LIGHT. INCLUDING FAN CONTROL SWITCH AND CONNECTIONS.	Item	74	38	18	18	0	0
LIGHTS								
1	LED EMERGENCY LIGHT WITH RED OR GREEN EXIT SIGN, 110V 60 HZ, TWO FLOODLIGHTS, 3500 °K, BATTERY DURATION 90 MINUTES MINIMUM, ADJUSTABLE FLOOD LIGHTS WALL MOUNTED.	Item	130	51	30	39	10	0
2	LED LIGHTING FIXTURE SURFACE MOUNTED 2' x 1', 20 WATTS, 110 LM/W MINIMUM EFFICACY, COLOR TEMPERATURE 3500 °K, CRI>80, 110V 60Hz. 60,000 LIFE EXPECTANCY MINIMUM. TWO LED BULBS. GROUND CONNECTION.	Item	29	6	0	23	0	0
3	OUTDOOR LED WALL LIGHT 110 V 60 HZ, 10 WATTS, 75 LM/W MINIMUM EFFICACY, COLOR TEMPERATURE 3000°K, CRI>75. 50,000 LIFE EXPECTANCY MINIMUM. INSTALLATION HEIGHT 24" OVER THE FLOOR LEVEL. RECTANGULAR SHAPE.	Item	150	60	26	56	8	0
4	LED LIGHTING FIXTURE SURFACE MOUNTED 4' x 1', 40 WATTS, 110 LM/W MINIMUM EFFICACY, COLOR TEMPERATURE 3500 °K, CRI>80, 110V 60Hz. 60,000 LIFE EXPECTANCY MINIMUM. TWO LED BULBS. GROUND CONNECTION.	Item	343	123	80	121	19	0
5	LED LIGHTING FIXTURE 4' x 1', 40 WATTS, 110 LM/W MINIMUM EFFICACY, COLOR TEMPERATURE 4500 °K, CRI>80, 110V 60Hz. 60,000 LIFE EXPECTANCY MINIMUM. TWO LED BULBS. GROUND CONNECTION. SUSPENDED FROM SLAB 36" WITH TWO RODS. COLOR FINISH WHITE.	Item	680	272	204	204	0	0
6	LED LIGHTING FIXTURE CEILING MOUNTED 2' x 2', 18 WATTS, 110 LM/W MINIMUM EFFICACY, COLOR TEMPERATURE 4500 °K, CRI>80, 110V 60Hz. 60,000 LIFE EXPECTANCY MINIMUM.	Item	4	0	0	0	4	0
7	LED LIGHTING FIXTURE CEILING MOUNTED 4' x 2', 36 WATTS, 110 LM/W MINIMUM EFFICACY, COLOR TEMPERATURE 4500 °K, CRI>80, 110V 60Hz. 60,000 LIFE EXPECTANCY MINIMUM.	Item	48	0	0	0	48	0
8	URBAN LIGHT ACCORDING TO ENGINEERING DRAWINGS. POLE TO BE VALMONT DS 340, ROUND, NONTAPERED STEEL POLE WITH HANDHOLE. CREE EDGE, ROUND AREA LUMINAIRE WITH PHOTOELECTRIC SENSOR.	Item	26	0	0	0	0	26