



SCOREBOARD SPECIFICATIONS

OVERALL DIMENSIONS

- 8' L x 4' W x 8" D

LOCATION

- Outdoor Scoreboards

COLOUR

- Royal Blue

WEIGHT

- Hanging weight: ≤ 200 lbs
- Shipping weight: ≤ 300 lbs

CONSTRUCTION

- 22-gauge galvanized steel cabinet with powder coat finish

POWER REQUIREMENTS

Scoreboard:

- (1) 20-amp, 120-volt, 60-hertz, grounded AC circuit connected to an ON/OFF switch and/or circuit breaker

Controller:

- Standard LCD controller powered by 12V AC Adapter or an optional internal battery.

SCORING INFORMATION DISPLAYED

- **HOME:** 2-digit displays, 0-99
- **GUEST:** 2-digit display, 0-9
- **CLOCK:** 4 – digit displays
- **PERIOD:** 1-digit display, 0-9
- **POSS:** 4 - 2.0" arrow display (optional)
- **BONUS:** 2 – 2.0" dot display

CAPTIONS

- **HOME, GUEST:** 6.0" tall
- **PERIOD:** 4.0" tall
- **BONUS:** 3.75 tall
- **POSS:** 3.0" tall (optional)
- **CLOCK COLON:** 1.75" tall

- **Polymeric Calendared Vinyl Lettering**

WARRANTY

The scoreboard should be warranted against defects in materials and workmanship for a period no less 5 year from the date of invoice.

INSTALLATION

- The scoreboard should mountable between (2) 8"(min) OD steel, schedule 40 poles; or (2) 8"(min) I-beams, minimum.
- Hole depth /diameter as well as pole/concrete specifications must be based on customer's local building codes, soil conditions, and wind loads. Mounting rails are supplied.


SCOREBOARD CONTROLLER

- The keyboard controller available with this scoreboard is microprocessor-controlled, molded of high-impact ABS plastic, has a tactile membrane keypad. Options include 900 MHz wireless control and internal battery pack with automatic battery charger.

SCOREBOARD ILLUSTRATION



Front View



Rear View

